

AGRIMAX RT 945

TIRE SIZE	380/90 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	159 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	380	RIM REC	W 12
OD (MM)	1852	RIM ALT	W 11; W 13
SLR (MM)	859	ECE	E4-106R-001409
RC (MM)	5699	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1785	2290	2790	3065	3295	3605	3875	4070	4375	-
40	1785	2290	2790	3065	3295	3605	3875	4070	4375	-
30	1910	2450	2990	3280	3530	3860	4150	4360	4685	-
10	2095	2735	3315	3955	4540	4715	5235	5815	6040	6565

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.