


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 650/75 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94512164	<b>RC (IN)</b>	228.2
<b>SW (IN)</b>	26.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	76.4	<b>RIM ALT</b>	DW 21 B
<b>SLR (IN)</b>	32.8	<b>ECE</b>	E11-106R-0010663

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	7610	8850	10100	11340	12590	13830
<b>FROM 40 TO 25</b>	8370	9730	11100	12470	13830	15210
20	8520	9920	11320	12710	14110	15510
12	8700	10120	11540	12960	14380	15820
5	9190	10700	12210	13710	15220	16730
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	11710	13620	15540	17460	19380	21300
5 HT	8520	9920	11320	12710	14110	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.