

# EARTHMAX SR 46

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 33.00 R 51                                                                               |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TOMBEREAU RIGIDE                                                                         |
| VERSION      | CUT RESISTANT COMPOUND                                                                   |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 235 B                                                                                    |



## DIMENSIONS US STANDARD

|          |          |             |           |
|----------|----------|-------------|-----------|
| CODE USA | 94061723 | RIM REC     | 24.00/5.0 |
| OD (IN)  | 120.1    | TRA CODE    | E4        |
| SLR (IN) | 55.2     | STAR RATING | ★★        |
| RC (IN)  | 369.2    |             |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 66000 | 68000 | 71500 | 74000 | 76000 | 78500 | 80500 | 82500 | 85500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.