

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>320/85 R 24</b> |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 122 A8/B           |

### DIMENSIUNI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 329  | <b>RIM REC</b> | W 11            |
| <b>OD (MM)</b>  | 1154 | <b>RIM ALT</b> | W 10 ; W 9      |
| <b>SLR (MM)</b> | 528  | <b>ECE</b>     | E11-106R-002976 |
| <b>RC (MM)</b>  | 3449 | <b>SRI</b>     | 550             |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 825  | 960  | 1095 | 1230 | 1365 | 1500 |
| <b>40</b>    | 825  | 960  | 1095 | 1230 | 1365 | 1500 |
| <b>30</b>    | 885  | 1030 | 1175 | 1320 | 1465 | 1605 |
| <b>10 LT</b> | 1110 | 1290 | 1470 | 1650 | 1830 | 2010 |
| <b>10 HT</b> | 885  | 1030 | 1175 | 1320 | 1465 | 1605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

