


# AGRIMAX RT 600



<b>TIRE SIZE</b>	<b>IF 680/85 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / ESPALHADOR / TRATOR / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D

## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94065486	<b>RC (IN)</b>	230.7
<b>SW (IN)</b>	26.9	<b>RIM REC</b>	DW23 B
<b>OD (IN)</b>	77.2	<b>RIM ALT</b>	DW21 B
<b>SLR (IN)</b>	33.3	<b>ECE</b>	E11-106R-006401

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>FROM 40 TO 25</b>	8020	9230	10590	11960	13330	14690	16060	17100
<b>20</b>	8340	9590	11010	12430	13860	15280	16700	17770
<b>12</b>	8660	9950	11430	12910	14380	15860	17340	18450
<b>5</b>	10180	11710	13450	15180	16920	18650	20390	21690
<b>UPTO 20 CYC</b>	10430	11990	13770	15540	17320	19090	20880	22210
<b>UPTO 10 CYC</b>	12430	14300	16410	18530	20650	22770	24890	26480
<b>5 HT</b>	8340	9590	11010	12430	13860	15280	16700	17770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.