

# POWER TRAX

|                     |                                    |
|---------------------|------------------------------------|
| <b>TIRE SIZE</b>    | <b>12.00 - 20</b>                  |
| <b>UM</b>           | IS STANDARD                        |
| <b>CONSTRUCTION</b> | ⊠ BIAS                             |
| <b>MACHINERY</b>    | MANIPULATOR DE CONTAINERE<br>GOALE |
| <b>VERSION</b>      | STANDARD                           |
| <b>TIRE TYPE</b>    | TT                                 |
| <b>LI/SS</b>        | 176 A5                             |



## DIMENSIONI IS STANDARD

|                |      |           |    |
|----------------|------|-----------|----|
| <b>SW (MM)</b> | 320  | <b>PR</b> | 20 |
| <b>OD (MM)</b> | 1150 |           |    |
| <b>RIM REC</b> | 8.5  |           |    |
| <b>RIM ALT</b> | 9.0  |           |    |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b>         | <b>10.00</b> |
|---------------------------|--------------|
| <b>25 LOAD WHEEL</b>      | 9230         |
| <b>25 STEER WHEEL</b>     | 7100         |
| <b>10 OTHER VEHICLES</b>  | 9230         |
| <b>25 OTHER VEHICLES</b>  | 7100         |
| <b>STATIC SIDE LOADER</b> | 10720        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.