

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>280/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	118 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94047499	<b>RC (IN)</b>	140.1
<b>SW (IN)</b>	11.5	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	46.7	<b>RIM ALT</b>	W 9
<b>SLR (IN)</b>	21.5	<b>ECE</b>	E4-106R-000614

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1610	1860	2130	2390	2660	2910
25	1610	1860	2130	2390	2660	2910
20	1720	2010	2280	2570	2840	3120
5 LT	2150	2500	2850	3210	2560	3900
5 HT	1720	2010	2280	2570	2840	3120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.