

AGRIMAX V-FLECTO

TYRE SIZE	VF 600/60 R 34
UM	US STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	160 D



DIMENSIONS US STANDARD

USA CODE	94074495	RIM REC	DW 20 B
SW (IN)	23.4	RIM ALT	DW 18 L ; DW 21 B
OD (IN)	62.4	ECE	E11-106R-008773
SLR (IN)	27.2	TRA CODE	R1W
RC (IN)	185.4	TREAD DEPTH (32nd)	64.89

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
45	4960	5780	6580	7400	8210	9030
FROM 40 TO 25	5460	6350	7240	8130	9030	9920
20	5560	6470	7390	8290	9200	10120
12	5670	6600	7530	8450	9380	10320
5	6000	6980	7960	8940	9920	10910
*UPTO 5 CYC WITH FRONT LOADER	7640	8880	10130	11390	12630	13890
5 HT	5560	6470	7390	8290	9200	10120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.