


AGRIMAX FORCE

TIRE SIZE	IF 600/70 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	165 D



DIMENSIUNI US STANDARD

USA CODE	94060047	RC (IN)	189.0
SW (IN)	23.7	RIM REC	DW 21 B; DW 21 A
OD (IN)	63.1	RIM ALT	DW 20 A; DW 20 B
SLR (IN)	27.9	ECE	E11-106R-006495

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4850	5570	6390	7230	8050	8870	9700	10330
FROM 40 TO 25	5330	6130	7030	7950	8850	9750	10670	11400
20	5540	6370	7310	8260	9200	10140	11090	11810
12	5750	6610	7590	8580	9560	10530	11520	12260
5	6770	7780	8930	10090	11230	12380	13550	14420
UPTO 20 CYC	6930	7960	9140	10330	11500	12680	13870	14760
UPTO 10 CYC	8270	9490	10890	12310	13710	15110	16530	17590
UPTO 5 CYC	9060	10420	11950	13500	15050	16580	18130	19300
5 HT	5540	6370	7310	8260	9200	10140	11090	11810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.