


AS 504

TIRE SIZE	27X10 - 15.3
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	95 A8
LI/SS FREE ROLLING	107 A8



РАЗМЕРЫ US STANDARD

USA CODE	94039500	RC (IN)	81.5
SW (IN)	10.2	RIM REC	9.00
OD (IN)	27.4	ECE	E4-106R-002324
SLR (IN)	12.5	PR	8

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	3010
15 FR	2560
20 FR	2400
25 FR	2150
5 DW	2130
15 DW	1810
20 DW	1710
25 DW	1520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.