DATA SHEET

PRINTED ON
23-04-2026

AW 702

TIRE SIZE	**10.5/65 - 16**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
VERSION	STANDARD
TIRE TYPE	TT
LI/SS FREE ROLLING	130 A8

DIMENSIUNI US STANDARD

USA CODE	94009275	**RC (IN)**	91.7
SW (IN)	10.6	**RIM REC**	W 9
OD (IN)	29.9	**RIM ALT**	W 8; W 8 L
SLR (IN)	13.8	**ECE**	E11-106R-003351

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	77
5 FR	5860
15 FR	4980
20 FR	4700
25 FR	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..