

# AGRIMAX FORCE

|                  |                                                  |
|------------------|--------------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 710/70 R 42 CFO</b>                        |
| <b>UM</b>        | US STANDARD                                      |
| <b>MACHINERY</b> | COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR |
| <b>VERSIÓN</b>   | STANDARD                                         |
| <b>TIRE TYPE</b> | TL                                               |
| <b>LI/SS</b>     | 179 D                                            |



## DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94040926 | <b>RC (IN)</b> | 242.8          |
| <b>SW (IN)</b>    | 28.2     | <b>RIM REC</b> | DW 25 B        |
| <b>OD (IN)</b>    | 81.1     | <b>RIM ALT</b> | DW 23 B        |
| <b>SLR (IN)</b>   | 36.2     | <b>ECE</b>     | E4-106R-001830 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>45</b>            | 7300  | 8390  | 9630  | 10880 | 12120 | 13370 | 14600 | 15540 |
| <b>FROM 40 TO 25</b> | 8020  | 9230  | 10590 | 11960 | 13330 | 14690 | 16060 | 17100 |
| <b>20</b>            | 8340  | 9590  | 11010 | 12430 | 13860 | 15280 | 16700 | 17770 |
| <b>12</b>            | 8660  | 9950  | 11430 | 12910 | 14380 | 15860 | 17340 | 18450 |
| <b>5</b>             | 10180 | 11710 | 13450 | 15180 | 16920 | 18650 | 20390 | 21690 |
| <b>UPTO 20 CYC</b>   | 10430 | 11990 | 13770 | 15540 | 17320 | 19090 | 20880 | 22210 |
| <b>UPTO 10 CYC</b>   | 12430 | 14300 | 16410 | 18530 | 20650 | 22770 | 24890 | 26480 |
| <b>UPTO 5 CYC</b>    | 13630 | 15670 | 18000 | 20330 | 22650 | 24980 | 27290 | 29040 |
| <b>5 HT</b>          | 8340  | 9590  | 11010 | 12430 | 13860 | 15280 | 16700 | 17770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.