


AGRIMAX FORCE

TIRE SIZE	IF 710/55 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D



DIMENSIONER IS STANDARD

SW (MM)	716	RIM REC	DW 25 B
OD (MM)	1646	ECE	E11-106R-005995
SLR (MM)	746	SRI	775
RC (MM)	4962	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
70	2290	2675	3000	3385	3765	4145	4640	4965	5460
FROM 65 TO 40	2520	2940	3300	3720	4140	4560	5100	5460	6000
30	2620	3055	3430	3865	4305	4740	5300	5675	6240
20	2720	3175	3560	4015	4470	4920	5505	5895	6480
10	3200	3730	4190	4720	5255	5970	6475	6930	7620
UPTO 30 CYC	3275	3820	4290	4835	5380	5925	6630	7095	7800
UPTO 15 CYC	3905	4555	5115	5765	6415	7065	7905	8460	9300
UPTO 10 CYC	4280	4995	5610	6320	7035	7750	8670	9280	10200
10 HT	2620	3055	3430	3865	4305	4740	5300	5675	6240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.