

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>340/85 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94021581	<b>RC (IN)</b>	139.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	46.8	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	20.9	<b>ECE</b>	E4-106R-000604

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	2010	2340	2660	2990	3320	3640
<b>25</b>	2010	2340	2660	2990	3320	3640
<b>20</b>	2150	2500	2850	3210	3560	3900
<b>5 LT</b>	2690	3130	3570	4010	4450	4880
<b>5 HT</b>	2150	2500	2850	3210	3560	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.