

AGRIMAX FORCE

TIRE SIZE	IF 800/70 R 38 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	184 D



DIMENSIONES US STANDARD

CÓDIGO USA	94055784	RC (IN)	243.5
SW (IN)	31.3	RIM REC	DW 27 B
OD (IN)	82.1	RIM ALT	DW 25 B, DW 28 B, DW 30 B
SLR (IN)	36.3	ECE	E11-106R-006497

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8480	9920	11360	12630	13900	14980	16790	18050
FROM 40 TO 25	9330	10910	12500	13890	15820	16470	18450	19800
20	9690	11340	13000	14440	15880	17120	19180	20630
12	10060	11780	13490	14990	16490	17780	19920	21430
5	11840	13860	15870	17640	19400	20910	23420	25200
UPTO 20 CYC	12110	14190	16250	18050	19850	21410	23980	25790
UPTO 10 CYC	14450	16910	19370	21530	23680	25520	28590	30750
UPTO 5 CYC	15850	18550	21240	23610	25970	27990	31360	33730
5 HT	9690	11340	13000	14440	15880	17120	19180	20630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.