DATA SHEET

PRINTED ON
22-04-2026

AW 708

TYRE SIZE	**500/50 - 17**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS / TRAILER
VERSION	STANDARD
TYRE TYPE	TL
LI/SS FREE ROLLING	140 A8

DIMENSIONS US STANDARD

USA CODE	94010363	**RC (IN)**	108.3
SW (IN)	19.7	**RIM REC**	16.00
OD (IN)	37.2	**ECE**	E4-106R-001884
SLR (IN)	16.4	**PR**	10

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	29
5 FR	7720
15 FR	6560
20 FR	6170
25 FR	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..