

# FLOTATION 648 T



<b>TIRE SIZE</b>	<b>550/45 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / MAȘINĂ DE RECOLTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	147 A8/144 B
<b>LI/SS FREE ROLLING</b>	159 A8/156 B

## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94052066	<b>RC (IN)</b>	126.1
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	42.1	<b>PR</b>	16
<b>SLR (IN)</b>	18.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	35	38	41
<b>5 FR</b>	12350	12930	13500
<b>10 FR</b>	11110	11640	12160
<b>20 FR</b>	9880	10350	10800
<b>25 FR</b>	8820	9240	9640
<b>30 FR</b>	7940	8310	8820
<b>5 DW</b>	8670	9090	9490
<b>10 DW</b>	7800	8180	8540
<b>20 DW</b>	6930	7270	7590
<b>25 DW</b>	6190	6490	6780
<b>30 DW</b>	5580	5840	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.