DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX RT 765

TIRE SIZE	**380/70 R 28**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	SPECIAL
TIRE TYPE	TL
LI/SS	127 D

DIMENSÕES US STANDARD

CÓDIGO USA	94063178	**RC (IN)**	152.9
SW (IN)	15.0	**RIM REC**	W 12
OD (IN)	50.9	**RIM ALT**	W 11; W 13
SLR (IN)	23.1	**ECE**	E11-106R-005829

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2130	2470	2820	3160	3520	3860
30	2240	2600	2970	3330	3690	4060
25	2340	2710	3100	3470	3860	4230
20	2450	2840	3250	3650	4050	4440
5 LT	2840	3320	3780	4240	4710	5170
5 HT	2450	2840	3250	3650	4050	4440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..