

FLOTATION V LINE

| | |
|---------------------------|-------------------------|
| TIRE SIZE | 550/60 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | SLÄPVAGN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 148 A8/144 B |
| LI/SS FREE ROLLING | 160 A8/ 156 B |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------|
| SW (MM) | 550 | RIM REC | AG 16.00 |
| OD (MM) | 1240 | PR | 12 |
| SLR (MM) | 540 | | |
| RC (MM) | 3725 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 1.80 | 2.10 |
|------------|------|------|------|
| 10 FR | 5175 | 5755 | 6300 |
| 20 FR | 4655 | 5180 | 5670 |
| 30 FR | 4140 | 4605 | 5040 |
| 40 FR | 3695 | 4110 | 4500 |
| 50 FR | 3325 | 3700 | 4000 |
| 10 DW | 3620 | 4030 | 4410 |
| 20 DW | 3255 | 3630 | 3970 |
| 30 DW | 2895 | 3225 | 3530 |
| 40 DW | 2585 | 2880 | 3150 |
| 50 DW | 2325 | 2590 | 2800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.