


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>420/80 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94075508	<b>RC (IN)</b>	234.4
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	76.8	<b>RIM ALT</b>	W 12
<b>SLR (IN)</b>	36.0	<b>ECE</b>	E11-106R-0010078

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	20	23	29	35	41	46	52	58	64
<b>30</b>	4880	5460	6140	6700	7390	8740	8630	9310	9890	10450	11350
<b>25</b>	4880	5460	6140	6700	7390	7840	8630	9310	9890	10450	11350
<b>20</b>	5240	5840	6570	7180	7900	8400	9250	9980	10580	11190	12160
<b>5 LT</b>	6550	7310	8220	8980	9900	10500	11570	12490	13250	14010	15220
<b>5 HT</b>	5240	5840	6570	7180	7900	8400	9250	9980	10580	11190	12160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.