


# AS 504

|                           |  |
|---------------------------|--|
| <b>TYRE SIZE</b>          | <b>7.00 - 12</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | IMPLEMENTS   |
| <b>VERSION</b>            | STANDARD   |
| <b>TYRE TYPE</b>          | TT   |
| <b>LI/SS DRIVE WHEEL</b>  | 83 A8  |
| <b>LI/SS FREE ROLLING</b> | 95 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |     |
|-----------------|------|----------------|-----|
| <b>SW (MM)</b>  | 187  | <b>RIM REC</b> | 4.5 |
| <b>OD (MM)</b>  | 683  | <b>PR</b>      | 6   |
| <b>SLR (MM)</b> | 300  |                |     |
| <b>RC (MM)</b>  | 2001 |                |     |

## LOAD CAPACITY (KG/TYRE)

| <b>KM/H / BAR</b> | <b>2.50</b> |
|-------------------|-------------|
| 10 FR             | 965         |
| 25 FR             | 820         |
| 30 FR             | 775         |
| 40 FR             | 690         |
| 10 DW             | 680         |
| 25 DW             | 575         |
| 30 DW             | 545         |
| 40 DW             | 485         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.