

AGRIMAX RT 855

TIRE SIZE	320/85 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	124 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94021574	RC (IN)	147.4
SW (IN)	13.0	RIM REC	W 11
OD (IN)	49.4	RIM ALT	W 9 ; W 10
SLR (IN)	22.4	ECE	E4-106R-000615

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3520
25	1940	2260	2580	2900	3220	3520
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.