


AW 711

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | IF 340/65 R 18 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HAY HARVESTER / IMPLEMENT MACHINERY / HARVESTER / IMPLEMENTS |
| VERSION | STUBBLE RESISTANT |
| TL/TT | TL |
| LI/SS | 153 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94053476 | RC (IN) | 106.4 |
| SW (IN) | 13.0 | RIM REC | W 11 |
| OD (IN) | 35.4 | ECE | E11-106R-002992 |
| SLR (IN) | 15.0 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-------------------------|------|------|------|------|------|------|------|------|------|
| FROM 5 TO 30 MPH | 2580 | 3380 | 4110 | 4750 | 5480 | 6210 | 6680 | 7330 | 8050 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.