

AGRIMAX RT 657

TIRE SIZE	320/65 R 18
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	125 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	310	RIM REC	W 10
OD (MM)	885	RIM ALT	W 9 ; W 11
SLR (MM)	400	ECE	E11-106R-008145
RC (MM)	2667	SRI	425

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.8	3.2
50	545	645	745	825	925	1010	1205	1340	1505	1650
40	545	645	745	825	925	1010	1205	1340	1505	1650
30	585	695	800	885	995	1080	1295	1435	1615	1770
10 LT	735	865	1000	1110	1245	1355	1620	1795	2020	2215
10 HT	585	695	800	885	995	1080	1295	1435	1615	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.