

AGRIMAX RT 765

TIRE SIZE	710/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	SPECIAL
TIRE TYPE	TL
LI/SS	175 D ; 178 A8



DIMENSÕES US STANDARD

CÓDIGO USA	94063536	RC (IN)	226.4
SW (IN)	28.2	RIM REC	DW 23 B
OD (IN)	77.1	ECE	E11-106R-006000
SLR (IN)	33.8	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
40	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210
30	6240	7350	8470	9420	10550	11510	12620	13580	14860	15970
25	6450	7610	8760	9750	10910	11900	13060	14050	15380	16530
20	6820	8060	9280	10330	11550	12600	13820	14870	16270	17490
5 LT	7960	9380	10810	12040	13460	14680	16110	17340	18970	20390
5 HT	6820	8060	9280	10330	11550	12600	13820	14870	16270	17490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.