


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>620/75 R 30 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / COLHEDORA DE ALGODÃO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94039586	<b>RC (IN)</b>	203.5
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	66.6	<b>ECE</b>	E4-106R-001420
<b>SLR (IN)</b>	30.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
<b>30</b>	5690	6550	8020	8770	9630	10490	11360	12350
<b>25</b>	5690	6550	8020	8770	9630	10490	11360	12350
<b>20</b>	6080	7010	8600	9390	10320	11240	12170	13220
<b>10 CYC</b>	9380	10800	13250	14470	15890	17320	18750	20370
<b>5 CYC</b>	10230	11780	14450	15780	17340	18890	20450	22220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.