


# AGRIMAX FORTIS

<b>TIRE SIZE</b>	<b>800/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 D ; 181 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94032969	<b>RC (IN)</b>	244.2
<b>SW (IN)</b>	31.4	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	82.1	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	35.9	<b>ECE</b>	E4-106R-001424

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	7940	9260	10420	11570	12730	13720	15210	16500
30	8330	9720	10950	12160	13370	14420	15970	17360
25	8730	10180	11460	12730	14010	15100	16730	18190
20	9130	10650	11980	13320	14650	15780	17490	19010
5 LT	10640	12410	13970	15510	17060	18400	20390	22160
5 HT	9130	10650	11980	13320	14650	15780	17490	19010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.