

# MULTIMAX MP 513

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 425/75 R 20 MPT  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | UNIVERSAL VEHICLE / FERTILIZER TRUCK / UNIVERSAL VEHICLE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 148 G  |



## DIMENSIONS US STANDARD

|                 |          |                |                                |
|-----------------|----------|----------------|--------------------------------|
| <b>USA CODE</b> | 94034703 | <b>RIM REC</b> | 13                             |
| <b>SW (IN)</b>  | 16.6     | <b>RIM ALT</b> | 13 SDC; 11 SDC; 12 SDC; 11; 12 |
| <b>OD (IN)</b>  | 45.1     | <b>ECE</b>     | E11-54R-0016141                |
| <b>RC (IN)</b>  | 136.4    |                |                                |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23   | 29   | 36   | 44   | 51   | 58   |
|-----------|------|------|------|------|------|------|
| 55        | 3390 | 3990 | 4740 | 5490 | 6220 | 6940 |
| 40        | 3690 | 4330 | 5150 | 5960 | 6750 | 7540 |
| 25        | 3910 | 4600 | 5460 | 6320 | 7150 | 7990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.