


# AT 171

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>35X9 - 20</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | ВЕЗДЕХОД / ТРАКТОР ДЛЯ ЕЗДЫ<br>ПО ГРЯЗИ / ТРАКТОР-ТЯГАЧ                                |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 85 A8 ; 61 F   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |       |
|-----------------|----------|----------------|-------|
| <b>USA CODE</b> | 94055173 | <b>RC (IN)</b> | 105.1 |
| <b>SW (IN)</b>  | 7.9      | <b>RIM REC</b> | W 7   |
| <b>OD (IN)</b>  | 35.2     | <b>RIM ALT</b> | W 6   |
| <b>SLR (IN)</b> | 16.5     | <b>PR</b>      | 6     |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI           | 20   | 15  |
|---------------------|------|-----|
| 25 MUD BOGGING      | 1135 | -   |
| 50 MUD BOGGING      | 567  | -   |
| 25 CASUAL TRANSPORT | -    | 940 |
| 50 CASUL TRANSPORT  | -    | 481 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.