

AGRIMAX RT 855

TIRE SIZE	320/85 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	122 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94044665	RC (IN)	134.8
SW (IN)	13.0	RIM REC	W 11
OD (IN)	45.4	RIM ALT	W 9; W 10
SLR (IN)	20.4	ECE	E4-106R-000613

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1820	2120	2410	2710	3010	3300
25	1820	2120	2410	2710	3010	3300
20	1950	2270	2590	2910	3230	3540
5 LT	2450	2840	3240	3640	4030	4430
5 HT	1950	2270	2590	2910	3230	3540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.