


# RIDEMAX IT 697 (M+S)

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>650/65 R 42 IND</b>                                                                   |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRATTORE                                                                                 |
| <b>VERSIONE</b>     | STANDARD                                                                                 |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 171 D ; 176 A8                                                                           |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94050109 | <b>RC (IN)</b> | 231.1          |
| <b>SW (IN)</b>    | 25.4     | <b>RIM REC</b> | DW 20 B        |
| <b>OD (IN)</b>    | 75.6     | <b>RIM ALT</b> | DW 18 L        |
| <b>SLR (IN)</b>   | 34.6     | <b>ECE</b>     | E4-106R-002659 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17   | 23   | 29    | 35    | 41    | 46    |
|-----------|------|------|-------|-------|-------|-------|
| 40        | 6370 | 7860 | 9210  | 10710 | 12070 | 13560 |
| 30        | 6890 | 8500 | 9960  | 11570 | 13040 | 14650 |
| 25        | 7350 | 9080 | 10650 | 12370 | 13930 | 15650 |
| 20        | 7650 | 9440 | 11070 | 12850 | 14480 | 16270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.