

AGRIMAX RT 955



AGRIMAX
RADIAL TRACTOR TIRES

AGRIMAX RT 955



AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø24"	210/90 R 24 (8.3 R 24)	107 A8/B	W 7	W 6	8.4	39.8	18.2	119.2	475	STD
Ø28"	210/95 R 28 (8.3 R 28)	116 A8/B	W 7	W 6	8.4	43.7	20.2	132.4	525	STD
Ø32"	210/95 R 32 (8.3 R 32)	120 A8/B	W 7	W 6	8.4	47.8	22.5	145.8	575	STD
	230/95 R 32 (9.5 R 32)	128 A8/B	W 7	W 8	9.0	49.3	23.0	150.0	600	STD
	270/95 R 32 (11.2 R 32)	136 A8/B	W 9	W 8 W 10	10.8	52.2	24.2	160.5	625	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
D	154 lbs		

Permissible tolerances: 0.0-2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0, outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	270/80 R 32	131 A8/B	W 9	W 8 W 10	10.6	48.2	22.4	146.1	600	STD
Ø36"	230/95 R 36 (9.5 R 36)	130 A8/B	W 7	W 8	9.0	53.2	25.2	161.9	650	STD
	270/80 R 36	134 A8/B	W9	W8 W10	10.8	53.0	24.8	161.0	650	STD
	270/95 R 36 (11.2 R 36)	139 A8/B	W 9	W 8 W 10	10.8	56.2	26.2	170.7	675	STD
Ø38"	270/95 R 38 (11.2 R 38)	140 A8/B	W 9	W 8 W 10	10.8	58.2	27.4	177.6	700	STD
Ø40"	230/95 R 40 (9.5 R 40)	132 A8/B	W 7	W 8	9.0	57.2	27.2	175.0	700	STD
Ø42"	230/95 R 42 (9.5 R 42)	133 A8/B	W 7	W 8	9.0	59.3	28.1	180.9	725	STD
	300/85 R 42 (11.2 R 42)	144 A8/B	W 9	W 10 W 11	11.6	62.1	29.3	190.9	750	STD
Ø44"	230/95 R 44 (9.5 R 44)	134 A8/B	W 7	W 8	9.0	61.3	29.1	188.5	750	STD
	270/95 R 44 (11.2 R 44)	142 A8/B	W 9	W 8 W 10	10.8	64.3	30.1	196.2	775	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	210/95 R 44 (8.3 R 44)	120 A8/B	W 7	W 6	8.4	59.8	28.4	183.2	725	STD
Ø46"	270/95 R 46 (11.2 R 46)	143 A8/B	W 9	W 8 W 10	10.8	66.3	31.2	203.5	800	STD
	340/85 R 46 (13.6 R 46)	150 A8/B	W 12	W 11	13.9	68.7	32.5	210.5	850	STD
	300/95 R 46 (12.4 R 46)	148 A8/B	W 9	W 10 W 11 DW 10 DW 11	11.6	68.4	32.0	209.4	825	STD
	300/95 R 46 (12.4 R 46)	148 D 151 A8	W 9	W 10 W 11 DW 10 DW 11	11.6	68.4	32.0	209.4	825	STD
Ø48"	230/95 R 48 (9.5 R 48)	136 A8/B	W 7	W 8	9.0	65.2	31.2	200.2	800	STD
	340/85 R 48 (13.6 R 48)	151 D 154 A8	W 12	W 11	13.9	70.7	33.7	219.4	875	STD
	230/95 R 48 (9.5 R 48)	136 D 139 A8	W 7	W 8	9.0	65.2	31.2	200.2	800	STD
	340/85 R 48 (13.6 R 48)	152 A8/B	W 12	W 11	13.9	70.7	33.7	219.4	875	STD
	270/95 R 48 (11.2 R 48)	144 A8/B	W 9	W 8 W 10	10.8	68.2	32.3	210.7	825	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø52"	300/95 R 52 (12.4 R 52)	151 A8/B	W 9	W 10 W 11 DW 10 DW 11	11.6	74.4	35.0	227.3	900	STD
Ø54"	270/95 R 54 (11.2 R 54)	146 A8/B	W 9	W 8 W 10	10.8	74.2	35.2	228.9	900	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
R1	D		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
154 lbs			

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026