

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>550/60 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8/144 B
<b>LI/SS FREE ROLLING</b>	160 A8/156 B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	550	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1260	<b>ECE</b>	E11-106R-004396
<b>SLR (MM)</b>	547	<b>PR</b>	12
<b>RC (MM)</b>	3640		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.80	2.10
10 FR	5175	5755	6300
20 FR	4655	5180	5670
30 FR	4140	4605	5040
40 FR	3695	4110	4500
50 FR	3325	3700	4000
10 DW	3620	4030	4410
20 DW	3255	3630	3970
30 DW	2895	3225	3530
40 DW	2585	2880	3150
50 DW	2325	2590	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.