

FLOTATION 648

TIRE SIZE	700/40 - 22.5
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	166 A8/ 162 B



РАЗМЕРЫ US STANDARD

USA CODE	94006489	RC (IN)	139.3
SW (IN)	27.6	RIM REC	AG 24.00
OD (IN)	46.1	ECE	E4-106R-002311
SLR (IN)	20.1	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
5 FR	14550	15480	16360
10 FR	13090	13930	14730
20 FR	11640	12380	13080
25 FR	10390	11060	11680
30 FR	9360	9950	10470
5 DW	10300	10950	11570
10 DW	9260	9840	10420
20 DW	8230	8750	9260
25 DW	7350	7810	8270
30 DW	6610	7030	7390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.