

# CON STAR

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>340/80 - 20</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | PALA COMPATTA / SOLLEVATORE<br>TELESCOPICO / PALA COMPATTA /<br>SOLLEVATORE TELESCOPICO |
| <b>VERSIONE</b>     | INDUSTRIAL  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 144 A8  |



## DIMENSIONI IS STANDARD

|                 |      |                |                                |
|-----------------|------|----------------|--------------------------------|
| <b>SW (MM)</b>  | 350  | <b>RIM REC</b> | 11                             |
| <b>OD (MM)</b>  | 1065 | <b>RIM ALT</b> | 12; 11 SDC; 12 SDC; W 10; W 11 |
| <b>SLR (MM)</b> | 491  | <b>ECE</b>     | E11-106R-003021                |
| <b>RC (MM)</b>  | 3272 | <b>SRI</b>     | 500                            |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 40                | 2800        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.