

AS 504

TIRE SIZE	5.00 - 15
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	75 A8
LI/SS FREE ROLLING	88 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	140	RIM REC	3.50 D
OD (MM)	657	RIM ALT	3.00 D; 4.00 E; 4 J
SLR (MM)	308	ECE	E4-106R-001950
RC (MM)	1957	PR	6

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.50
10 FR	785
25 FR	665
30 FR	625
40 FR	560
10 DW	540
25 DW	460
30 DW	430
40 DW	385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.