

## RT 851



# RT 851



RT 851 is a R-1 tire specially engineered for tractors in grassland applications. The special rounded lug design has been developed to reduce any damage to grassland and emerging crops as well as soil compaction. The strong nylon casing with rugged polyester belts provides extraordinary traction as well as increased load capacity.



| SIZE | US CODE                   | LI/SS    | RIM                                                                               |                                                                                   | SW<br>(in)           | OD<br>(in) | SLR<br>(in) | RC<br>(in) | SRI<br>index | VERSION |     |
|------|---------------------------|----------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------------------|------------|-------------|------------|--------------|---------|-----|
|      |                           |          | REC RIM                                                                           | ALT RIM                                                                           |                      |            |             |            |              |         |     |
|      |                           |          |  |  |                      |            |             |            |              |         |     |
| Ø20" | 14.9 L R 20 (375/75 R 20) | 94048632 | 119 A8/B                                                                          | W 13                                                                              | W 11<br>W 12<br>W 14 | 14.9       | 43.3        | 19.6       | 129.4        | 525     | STD |

STD: STANDARD

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| A8/B                                                                                |                                                                                     | 119 lbs                                                                             |                                                                                     |

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index