

# TR 315

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>26X12.00 - 12</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | ARBETSFORDON / SKÖRDEMASKIN<br>FÖR FRUKTODLING /<br>DIKNINGSMASKIN / SKÖRDEMASKIN /<br>ARBETSFORDON |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94022373 | <b>RC (IN)</b> | 75.0            |
| <b>SW (IN)</b>  | 12.1     | <b>RIM REC</b> | 10½ JA          |
| <b>OD (IN)</b>  | 25.8     | <b>RIM ALT</b> | 8½ JA; 9½ JA    |
| <b>SLR (IN)</b> | 11.4     | <b>ECE</b>     | E11-106R-003494 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>20</b> |
| 10               | 1760      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.