

# FLOTATION 648

<b>TYRE SIZE</b>	<b>700/50 - 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	157 A8/154 B
<b>LI/SS FREE ROLLING</b>	169 A8/165 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	700	<b>RIM REC</b>	24.00
<b>OD (MM)</b>	1373	<b>ECE</b>	E4-106R-002278
<b>SLR (MM)</b>	621	<b>PR</b>	12
<b>RC (MM)</b>	4099		

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.50	1.60	1.80
<b>10 FR</b>	7300	7580	8120
<b>20 FR</b>	6570	6825	7310
<b>30 FR</b>	5840	6065	6495
<b>40 FR</b>	5215	5415	5800
<b>50 FR</b>	4695	4875	5150
<b>10 DW</b>	5195	5390	5775
<b>20 DW</b>	4675	4850	5200
<b>30 DW</b>	4155	4310	4620
<b>40 DW</b>	3710	3850	4125
<b>50 DW</b>	3340	3465	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.