


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>425/55 R 17 MPT</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEHÍCULO UNIVERSAL / CAMIÓN DE FERTILIZANTES / VEHÍCULO UNIVERSAL
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 A8/B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94065110	<b>RC (IN)</b>	106.5
<b>SW (IN)</b>	16.6	<b>RIM REC</b>	13
<b>OD (IN)</b>	35.4	<b>RIM ALT</b>	13.00
<b>SLR (IN)</b>	15.7	<b>ECE</b>	E11-106R-006433

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	51	58
30	2280	2810	3340	3800	4330	4850	5380	5840
25	2280	2810	3340	3800	4330	4850	5380	5840
20	2450	3010	3570	4080	4640	5200	5580	6260
15	2540	3120	3700	4220	4810	5390	5790	6490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.