

# TR 463

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>16.9 - 28</b>      |
| <b>UM</b>           | IS STANDARD           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                |
| <b>MACHINERY</b>    | GRÄVLASTARE / TRAKTOR |
| <b>VERSION</b>      | INDUSTRIAL            |
| <b>TIRE TYPE</b>    | TL                    |
| <b>LI/SS</b>        | 152 A8                |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 450  | <b>RIM REC</b> | DW 15 L         |
| <b>OD (MM)</b>  | 1405 | <b>RIM ALT</b> | DW 14 L         |
| <b>SLR (MM)</b> | 636  | <b>ECE</b>     | E11-106R-003626 |
| <b>RC (MM)</b>  | 4190 | <b>PR</b>      | 12              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.60</b> |
| 40                | 3550        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.