DATA SHEET

PRINTED ON
23-04-2026

TR 882

TIRE SIZE	**400/60 - 15.5**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

ABMESSUNGEN US STANDARD

USA-CODE	94019861	**RC (IN)**	102.6
SW (IN)	15.7	**RIM REC**	AG 13.00
OD (IN)	34.4	**ECE**	E4-106R-001879
SLR (IN)	14.9	**PR**	14

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6170
15 DW	5250
20 DW	4940
25 DW	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..