

FLOTATION RIB 774

550/60 - 22.5

| | |
|--------------|---|
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BIÇERDÖVER / RÖMORK / BIÇERDÖVER / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 167 A8/163 B |



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 550 | RIM REC | AG 16.00 |
| OD (MM) | 1240 | ECE | E11-106R-005942 |
| SLR (MM) | 540 | PR | 16 |
| RC (MM) | 3725 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.40 | 2.60 | 2.80 |
|------------|------|------|------|
| 10 FR | 6970 | 7310 | 7630 |
| 20 FR | 6275 | 6575 | 6865 |
| 30 FR | 5580 | 5845 | 6105 |
| 40 FR | 4980 | 5220 | 5450 |
| 50 FR | 4480 | 4700 | 4875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.