


# RIDEMAX FL 690

<b>TIRE SIZE</b>	<b>30.5L R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA / REMOLQUE
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	184 A8 ; 181 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94033836	<b>RC (IN)</b>	213.8
<b>SW (IN)</b>	31.1	<b>RIM REC</b>	DH 27 B
<b>OD (IN)</b>	70.9	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	31.7	<b>ECE</b>	E11-106R-002986

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	44
30	8370	9640	11640	12550	14370	16000	17460	18190
25	9630	11090	13390	14440	16530	18420	20090	20920
20	10880	12530	15130	16320	18680	20810	22710	23640
15	11470	13220	15960	17210	19700	21930	23930	24920
5	13320	15330	18520	19960	22850	25460	27780	28920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.