


# AGRIMAX V- FLECTO

TIRE SIZE	VF 480/70 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	153 D



## DIMENSÕES US STANDARD

CÓDIGO USA	94512775	RC (IN)	171.4
SW (IN)	19.5	RIM REC	W 18 L
OD (IN)	56.3	RIM ALT	W 16 L; DW 18 L
SLR (IN)	25.4	ECE	E11-106R-0010762

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4020	4670	5330	6000	6660	7320
FROM 40 TO 25	4420	5150	5860	6590	7320	8050
20	4510	5250	5990	6720	7460	8200
12	4600	5350	6110	6860	7610	8370
5	4860	5650	6460	7250	8050	8850
*UPTO 10 CYC WITH FRONT LOADER	6190	7210	8220	9240	10250	11260
10HT	4510	5250	5990	6720	7460	8200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.