

# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/80 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94518647	<b>RC (IN)</b>	245.0
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	80.2	<b>RIM ALT</b>	DW 15 L
<b>SLR (IN)</b>	37.3	<b>ECE</b>	E11-106R-004757

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
<b>45</b>	5750	6690	7620	8710	9640	10570	11660	12280	13520	14620	15540
<b>FROM 40 TO 25</b>	6330	7350	8380	9570	10590	11620	12820	13500	14870	16060	17080
<b>20</b>	6450	7500	8540	9770	10810	11860	13070	13770	15170	16390	17430
<b>12</b>	6580	7650	8710	9950	11020	12090	13330	14040	15460	16710	17770
<b>5</b>	6960	8090	9210	10530	11660	12790	14100	14850	16360	17670	18790
<b>UPTO 20 CYCLIC</b>	7180	8340	9500	10870	12030	13190	14550	15320	16880	18230	19390
<b>UPTO 10 CYCLIC</b>	8560	9950	11340	12960	14350	15740	17360	18290	20140	21760	23150
<b>UPTO 5 CYCLIC</b>	9390	10910	12430	14210	15730	17250	19020	20040	22070	23840	25360
<b>5 HT</b>	6450	7500	8540	9770	10810	11860	13070	13770	15170	16390	17430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.