

EARTHMAX SR 468



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 468



EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation. EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø49"	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	269	28.9	107.1	48.6	328.8	104.58	CR
	27.00 R 49	TL	E4	***	226 B	19.50/4.0	-	346	28.9	107.1	48.6	328.8	104.58	STD
	27.00 R 49	TL	E4	**	223 B	19.50/4.0	-	314	28.9	107.1	48.6	328.8	104.58	STD
	27.00 R 49	TL	E4	***	226 B	19.50/4.0	-	296	28.9	107.1	48.6	328.8	104.58	CR
Ø57"	50/80 R 57	TL	E4	**	257 B	32.00/6.0	29.00/6.0 34.00/6.0	651	47.4	142.1	62.9	428.0	120.96	CR

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
B	257 lbs		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
40.00 R 57	TL	E4	**	250 B	29.00/6.0	32.00/6.0	651	44.3	140.7	62.8	421.3	126	STD
40.00 R 57	TL	E4	**	250 B	29.00/6.0	32.00/6.0	548	44.3	140.7	62.8	421.3	126	CR
37.00 R 57	TL	E4	***	249 B	27.00/6.0	29.00/6.0	754	40.6	134.8	59.8	406.1	110.88	HRC
37.00 R 57	TL	E4	**	245 B	27.00/6.0	29.00/6.0	582	40.6	134.8	59.8	406.1	110.88	STD
37.00 R 57	TL	E4	**	245 B	27.00/6.0	29.00/6.0	699	40.6	134.8	59.8	406.1	110.88	HRC
46/90 R 57	TL	E4	**	252 B	29.00/6.0	32.00/6.0	798	44.9	140.7	62.6	425.2	126	HRC
37.00 R 57	TL	E4	**	245 B	27.00/6.0	29.00/6.0	497	40.6	134.8	59.8	406.1	110.88	CR
40.00 R 57	TL	E4	**	250 B	29.00/6.0	32.00/6.0	774	44.3	140.7	62.8	421.3	126	HRC
50/80 R 57	TL	E4	**	257 B	32.00/6.0	29.00/6.0 34.00/6.0	918	47.4	142.1	62.9	428.0	120.96	HRC
46/90 R 57	TL	E4	**	252 B	29.00/6.0	32.00/6.0	671	44.9	140.7	62.6	425.2	126	STD

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
  B	 E4  257 lbs		Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
46/90 R 57	TL	E4	**	252 B	29.00/6.0	32.00/6.0	565	44.9	140.7	62.6	425.2	126	CR
50/80 R57	TL	E4	**	257 B	32.00/6.0	29.00/6.0 34.00/6.0	774	47.4	142.1	62.9	428.0	120.96	STD

CR: CUT RESISTANT COMPOUND, STD: STANDARD, HRC: HEAT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
 E4  B	 257 lbs	      	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026