

AGRIMAX RT 600

TIRE SIZE	540/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	142 D ; 145 A8



РАЗМЕРЫ US STANDARD

USA CODE	94053704	RC (IN)	165.4
SW (IN)	20.9	RIM REC	W 16 L
OD (IN)	55.6	RIM ALT	W 18 L
SLR (IN)	25.3	ECE	E11-106R-002980

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	3270	3860	4390	4920	5380	5840
30	3440	4060	4610	5160	5650	6140
25	3580	4220	4790	5380	5890	6390
20	3770	4440	5050	5650	6190	6720
5 LT	4400	5180	5890	6590	7220	7840
5 HT	3770	4440	5050	5650	6190	6720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.