

AGRIMAX RT 765

TIRE SIZE	420/70 R 30
UM	US STANDARD
MACHINERY	PULVERIZADOR / TRACTOR / VENDIMIADORA / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	134 D



DIMENSIONES US STANDARD

CÓDIGO USA	94063185	RIM ALT	W 12 ; W 14 L
SW (IN)	16.5	ECE	E11-106R-005830
OD (IN)	55.0	TRA CODE	R1W
SLR (IN)	24.8	TREAD DEPTH (32nd)	54.81
RC (IN)	164.3	TMPH (TM/H)	0
RIM REC	W 13		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2580	3000	3420	3840	4250	4670
30	2710	3150	3590	4030	4480	4920
25	2820	3280	3750	4210	4670	5130
20	2970	3450	3940	4420	4910	5380
5 LT	3450	4020	4590	5150	5710	6270
5 HT	2970	3450	3940	4420	4910	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.