


BK-LOADER 53

| | |
|---------------------|--|
| TYRE SIZE | 365/365 R 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | LOADER |
| VERSION | ARAMID BELTED |
| TYRE TYPE | TL |
| LI/SS | 146A2/142A4 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----|
| SW (MM) | 360 | RIM REC | 11 |
| OD (MM) | 990 | | |
| SLR (MM) | 458 | | |
| RC (MM) | 3017 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.5 | 2.0 | 2.5 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 5.5 |
|---------------------|------|------|------|------|------|------|------|------|------|
| 20 TRANSPORT | 930 | 1195 | 1405 | 1620 | 1855 | 2045 | 2255 | 2440 | 2650 |
| 10 LOADING | 1050 | 1350 | 1590 | 1830 | 2100 | 2310 | 2550 | 2760 | 3000 |
| STATIC | 1670 | 2150 | 2530 | 2910 | 3340 | 3675 | 4055 | 4390 | 4770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.